

NO.	Name	Model	N.W. (kg)	Length (mm)	Main Journal (mm)	Rod Journal (mm)	Stroke (mm)
1	LAND ROVER	TDV6(2.7L)	16.9	422.5	70	63	44
2		TDV6(3.0L) diesel	16.9	422.5	70	63	45
3		TDV6(3.0L) gasoline	17.1	553.5	70	56	44.5
4		TDV8(5.0)	20.3	553.5	70	56	46.5
5		AJ200	13	475	55	50	46
6		AJ200D	16.8	475	59	55	46
7	BMW	N57D30	19	630.5	55	50	45
8		N46	14.6	423.5	56	50	45
9		N47	13	451	55	50	45
10		N12/13/14/18	11	387.5	45	45	43
11		N20	13.6	431	50	50	44.8
12		B48	16.8	448.3	50	50	47.3
13		N52(2.5)	20.7	606	56	50	39.5
14		N52(3.0)	21.6	606	56	50	44
15		N54	22.5	606	56	50	45
16		N55	19.8	606	56	50	44.8
17		N63	19.6	569	65	54	44.2
18		M54B30	19.8	606	56	50	44.8
19	MERCEDES-BENZ	112940(3.2)	17.6	468.95	64	52	42
20		112912(2.6)	16	468.95	64	52	34
21		113940(AMG5.5)	20.2	575	64	52	42
22		OM651(8扇)	21	459	60	52	49.5
23		OM651(4扇)	21	459	60	52	49.5
24		OM642	22	491.5	76	64	46
25		OM646	17.4	519.5	58	48	44.2
26		OM271	14.6	468	55	48	42.5
27		OM272(3.5)	17.2	470.4	64	52	43
28		OM274(2.0)	16.2	464	55	48	46
29		OM276	17.3	472.6	64	52	43
30	FORD	F150(6.0)	34.9	638.5	81	69	52.5
31		6.4	37.3	638.5	81	72	52.5
32		6.7	39.8	708	81	72	54
33		1.6T	10.3	480.5	48	44	40.7
34		2.0T	15	474.5	60	50	45
35	AUDI	EA888(2.0)					
36		3.0T	16	407.3	65	56	44.5
37		3.2	20.6	492.75	60	54	47.8
38	JEEP	切诺基3.0	20.5	443	74	67.5	46
39	TOYOTA	1GR老	20.8	481	72	56	47.5
40		1GR	20.8	481	72	56	47.5
41		1UZ/2UZ/3UZ	24	616	67	52	41.25
42		1VD					
43	NISSAN	VQ25	16.3	481.5	60	45	34.5
44		VQ35	19	481.8	60	52	40.7
45		V9X	23.3	513.4	74	67	45
46	LEVANTE	3.0T	20.3	472.6	68	54	42.25

NO.	Name	Model	N.W. (kg)	Length (mm)	Main Journal (mm)	Rod Journal (mm)	Stroke (mm)	
47	HYUNDAI	D4BB	18.6	555	66	53	50	
48		D4CB	22	555	67	57	48	
49		G488	15.1	492	52	48	48.5	
50	FIAT	480	25.25	528	79.8	63.7	57.7	
51	CHEVROLET	1.5L	12	445	49	40	42.5	
52	GM	GM6.5-V8	31.5	683.5	75	61	48.5	
53	SUZUKI	F6A	6	340	44	36	33	
54	JCB	3CX(444)	41	621	88	73	66	
55		4CX(448)	41	621	88	73	67	
56	KAMAZ	MTZ80	32	723	75.1	68.1	62.5	
57	CAT	320D/C6.4	50.4	925	90	65	65	
58		3054C	32	610	75.2	67	62.5	
59		C4.2	35.2	655.5	90	65	65	
60		C4.4/1104	32	609.7	76.2	68	63.5	
61		C4.4/1104(花键)	27.3	617.7	76.2	63.5	63.5	
62		3046	39.35	802.5	78	58	60	
63		3304	58.8	776.65	88.9	76.2	76.2	
64		3306	76.2	1073.8	88.9	76.2	76.2	
65		S4KT	34.25	654	90	60	65	
66		S6KT	51	925	90	60	65	
67		C7/3116/3126	62	863.5	90	70	63.35	
68		C9	74.5	914	104	80	74.5	
69		C13	108.5	1088	107.5	88.05	78.5	
70		MITSUBISHI	4D30/4D31(6孔)	27.05	682.5	78	60	52.5
71			4D32(9孔)	26.75	682.5	78	60	52.5
72	4D33(14*1.5)		27.9	682.5	78	60	57.5	
73	4D34(12*1.25)内键/外键		27.9	682.5	78	60	57.5	
74	4D34T		28.5	682.5	78	65	57.5	
75	4D35		28.5	682.5	78	65	60	
76	4D55		19	554.5	66	53	45	
77	4D56U		19.5	554.5	66	57	47.5	
78	4D56/D4BA		18.85	554.5	66	53	47.5	
79	4D56T		18.75	555	66	53	50	
80	4M40		18.5	582	68	54	50	
81	6D14/6D15		54.25	1011	80	65	57.5	
82	6D16		53.8	969	80	65	57.5	
83	6D16T(6M60)		56.7	969	84	70	57.5	
84	6D16T-2		55	969	84	65	57.5	
85	6D17		57.4	969	80	65	62.5	
86	6D20/6D22		94.3	1140	100	84	70	
87	6D24		101	1136	100	84	75	
88	6D31		40.5	922.5	78	60	52.5	
89	6D34		43.5	925.5	78	65	57.5	
90	6D40		100	1166	100	84	70	
91	6DB1		84	1157	90	75	75	
92	8DC9/8DC91/8DC92		95.8	933.5	100	90	70	
93	S4E		23.15	614	75	58	47	
94	MITSUBISHI		S4F	22.5	614	75	58	49
95		S4Q	18.5	544	65	58	51.5	

NO.	Name	Model	N.W. (kg)	Length (mm)	Main Journal (mm)	Rod Journal (mm)	Stroke (mm)
96		S4S	27	587.5	78	58	60
97		S6S	39.35	802.5	78	58	60
98	ISUZU	4BB1	29.8	647.5	76	64	55
99		4LE2(直喷)	15.6	500.5	60	46	49
100		4LE2(电喷)	15.6	500.5	60	46	48
101		4BC2/DB33	26.45	647.5	76	64	50
102		4BD1	32.8	647.5	80	64	59
103		4BE1	31	647.5	76	64	52.5
104		4BG1	37.95	647.5	80	64	62.5
105		4DA1	21.5	563	70	53	51
106		4HF1	37.2	660	82	66	55
107		4HG1	37.05	660	82	66	55
108		4HK1/4HE1T	45.8	662.5	82	73	62.5
109		4JA1	18.7	563	60	53	46
110		4JB1	21.7	563	70	53	51
111		4JB1T	22	563.5	70	53	51
112		4JG1/4JG2	24.3	564.5	70	53	53.5
113		4JJ1	22.6	563.5	70	53	52
114		4JJ1-1	22.6	563.5	70	53	53
115		4JJ1(小头带6孔)	23	563.5	70	53	53
116		4JK1	22.5	563	70	53	43.6
117		4ZA1	13.5	508.5	56	49	37.5
118		4ZB1	16	507	56	49	41
119		4ZD1	18.25	507	56	49	45
120		4ZE1	16	507	56	49	47.5
121		江铃国③	21	563	70	53	51
122		4KH1/600P	21.5	563	70	53	52
123		C190	16.9	563	60	53	42
124		C223	17.1	561	60	53	46
125		C240	21.65	565	70	53	51
126		6BB1(NEW)	43.1	891	80	64	55
127		6BB1(NEW花键)	43.1	891	80	64	55
128		6BB1(OLD)	42.2	891	76	64	55
129		6BD1	44.75	892	80	64	59
130		6BD1T/DB58/6BF1	48.95	889	80	64	59
131		6BG1/6BG1T	44.5	892	80	64	62.5
132		6HE1	53	915	82	66	62.5
133		6HK1/6HE1T	55	915	82	73	62.5
134		6HH1	52.5	915	82	66	66
135		6RB1	104.5	1238	100	90	80
136		6SA1	59	960	90	78	67.5
137		6SD1	81	960	90	80	72.5
138	6WA1	112	1232.5	105	92	72.5	
139	6WG1	109	1232.5	105	92	77	
140	6WF1	110	1232.5	105	92	70	
141	ISUZU	10PC1	86	935.5	97	78	67.5
142		10PE1/10PD1	92.6	933	105	82	75
143		12PC1	81.5	1080.5	97	78	67.5
144		12PD1	97.7	1080.5	105	82	75
145		4D130/4D120	67	963	95	75	90

NO.	Name	Model	N.W. (kg)	Length (mm)	Main Journal (mm)	Rod Journal (mm)	Stroke (mm)
146	KOMATSU	4D95E/4D95S	23.3	579.5	70	57	47.5
147		S4D95/S4D95L	22.65	578	70	57	57.5
148		S6D95	35.9	796	70	57	57.5
149		S4D102/4BT	34	617	83	69	60
150		S6D102/6BT	49.15	857	83	69	60
151		S6D105	50.7	974	85	66	62.5
152		S6D108	61.4	975	95	70	65
153		S6D110	52	974	85	66	62.5
154		S6D114(电喷)/6CT	66.5	967.5	98	76	67.5
155		S6D125	98.3	1105	110	80	75
156		S6D140	151	1244	120	90	82.5
157		HINO	EF750	97	917.5	110	84
158	EF750-II/EF750T		104	999	110	84	71
159	EH700		45.7	944	74	65	56.5
160	EK100		96.5	1272.5	90	84	75
161	K13C		89	1272.5	90	84	75
162	EK100-II/EK100T		100.2	1349.5	90	84	75
163	H07CT/H06CT/H07C		45.9	943	80	65	59
164	H07D		51.55	943	80	65	65
165	J05C/J05E/S05D		36.25	638	80	65	65
166	J08C/J08E		52.9	891.5	80	65	65
167	P11C(尖)		71.5	999.5	90	80	75
168	P11C(平)		75	1021.5	90	80	75
169	EM100		64	994	90	75	65
170	EP100		64	994	90	75	65
171	W04D/EM505(6孔)		30.9	651.5	73	62	59
172	W04D/EM505(8孔)		30.9	651.5	73	62	59
173	N04C		30.9	651.5	73	62	59
174	W06D		49	881	73	62	56.5
175	W06E		50	881	73	62	59
176	DCEC		4H	46.5	740	86	74
177		4BT	34	617	83	69	60
178		6BT	49.15	857	83	69	60
179		6CT	66.5	967.5	98	76	67.5
180		B3.3(M16)	22.65	578	70	57	57.5
181		B3.3(M18)	22.65	578	70	57	57.5
182		A2300	16.2	536.5	54	50	47
183		NT855	140	1299	114.3	79.37	76.2
184		NH220	129.6	1316	114.3	79.37	76.2
185		M11	93	1098	114	79	73.5
186		K19	169	1324.8	139.7	101.6	79.37
187		ISF2.8L	24.3	543.5	74	59	50
188	DCEC	ISF3.8L	34.7	678	83	69	57.5
189	PERKINS	4.236/4.248/MF265	23.75	617.3	76.2	63.5	63.5
190		4.203/D4.203	27.7	619	65	60	50
191		1104/C4.4	32	609.7	76.2	68	63.5
192		D3.152(D1-2101)MF240	17.5	490.85	69.8	57.1	63.5
193		3.152(花键)	17.5	490.85	69.8	57.1	63.5
194		3.152(D1-2100)	16.5	488.5	69.8	57.1	63.5
195		NE6	55.9	1022.5	90	70	65

NO.	Name	Model	N.W. (kg)	Length (mm)	Main Journal (mm)	Rod Journal (mm)	Stroke (mm)	
196	NISSAN	ND6	54.2	1022.5	90	70	60	
197		FD6	55	922	76	62	60	
198		FD6T	55.6	922	76	62	60	
199		FE6	51.1	918	78	65	63	
200		FE6T	51.65	927	78	65	63	
201		H20-2/K21/K50	15.65	553	63	48	41.5	
202		H20		553	63	52	41.5	
203		k25/K24	15.4	553	63	45	50	
204		PD6	95.5	1180	100	80	70	
205		PE6/PD6T	96	1180	100	80	70	
206		RD8	85	1013.7	110	85	62.5	
207		RE8(锥头10孔)	78	966	110	85	66	
208		RE8(圆头10孔)	78	966	110	85	66	
209		RE8(锥头9孔)	78	966	110	85	66	
210		RE8(圆头9孔)	78	966	110	85	66	
211		RF8(锥头)	90.5	1016	110	85	71	
212		RF8(圆头)	92.5	944	110	85	71	
213		RF10(锥头)	114.5	1195.5	110	85	71	
214		RF10(圆头)	115	1145	110	85	71	
215		TD27	23.25	581.6	71	57	46	
216		YD25T	17.3	518.5	63	52	50	
217		TD42	30.4	810.25	71	57	48	
218		ZD30	21.1	600	71	57	51	
219		YANMAR	4TNV94/98	19.5	553	65	58	55
220			4TNE94/98/4D94E	19.6	554	65	58	50
221			4TNV84/88	13.15	512	50	48	45
222			4TNE84/88	13	512	50	48	40
223			3TNV70	9.5	359.3	47	38	37
224	3NV76		10.1	397	47	43	42	
225	3TNV80		9.5	396.5	47	43	43	
226	4D106/4TNV106		29	604	76	64	62.5	
227	4D122		32	610	76.2	68	63.5	
228	TOYOTA	1DZ	20	510.5	65	50.5	53.5	
229		1FZ-1	37	803	69	57	52.5	
230		1FZ	37	803	69	57	47.5	
231		1HZ(新款)	33.6	788	67	59	50	
232		1HD-T/1HZ	33.6	788	67	59	50	
233		1KZ	21.4	608	70	59	51.5	
234		1RZ/2RZ	19.1	572	60	53	43	
235	TOYOTA	1GR	20.8	481	72	56	47.5	
236		1UZ/2UZ/3UZ	24	616	67	52	41.25	
237		1Z	27.4	599	74	55	51	
238		2L(6孔)	17.7	598	62	53	46	
239		2L-II	17.7	598	62	53	46	
240		2LT(8孔)	20.5	599	62	53	46	
241		2Z	28.2	587	74	55	57.5	
242		3L/5L	21.5	606	62	55	48	
243		3L(A)	21.7	598.5	62	55	48	
244		3RZ	22.5	572	60	53	47.5	
245		3SZ	10.6	404	46	42	45.8	

NO.	Name	Model	N.W. (kg)	Length (mm)	Main Journal (mm)	Rod Journal (mm)	Stroke (mm)
246		3Y	16.1	552	58	48	43
247		4Y	15.9	552	58	48	43
248		11Z/13Z	36.4	820.5	74	55	51
249		12R	18	565	58	50	39
250		13B	26.8	635.5	70	61	52.5
251		14B	29.6	635	70	61	56
252		12Z/14Z/15Z	35	815	74	55	57.5
253		21R/22R	19	587	60	53	44.5
254	DEAWOO	DB58	48.95	889	80	64	59
255		D2366/DE12	90.8	1016	96	83	77.5
256		D1146/DE08	64.35	925.5	84	71	69.5
257	KUBOTA	V2203	16	596	60	47	46.2
258		V2403	16	596	60	47	51
259		V3300	23.5	601.5	75	53	55
260		V3307	23	542.5	80	50	60
261		V3800	25.4	601.5	75	53	60
262		V2607	21.7	522.5	73	47	55
263		D1703	14	501	60	47	46.2
264	VOLVO	TD100A/101	96	1156	100	86	70
265		TD121	121	1216	108	92	75
266		D12D	110	1204	108	92	75
267		D13C	110	1150.5	108	99	79
268		D13D	110	1150.5	108	98	79
269	MAZDA	WL	20.2	556.5	67	55	46
270		SH	27	581.5	75.8	61	57
271		SL	24	582	75.8	61	55
272	IVECO	3.0L	23.35	563	76	64	52
273		2.3L	17.3	494	主76.2其余	59	47
274		2.8L	23.5	531	80.2	56.5	50